

SIT Parts Quick Reference

| Remotes | | | | Key | |
|-----------|---------|------------|--|-----------|---------------------------------------|
| Part #s | Version | System | Additional Info | | |
| 0.584.021 | GT | Proflame 1 | Hand Held - Silver | | Continuous Pilot Ignition (millivolt) |
| 0.584.022 | GTM | Proflame 1 | Hand Held - Silver | CPI | |
| 0.584.023 | GTMF | Proflame 1 | Hand Held - Silver | Highlight | Items we sell |
| 0.584.026 | GTMFS | Proflame 1 | Hand Held - Silver | | |
| 0.584.027 | GTMFS | Proflame 1 | Hand Held - Black | | |
| 0.584.046 | GT | Proflame 2 | Wall Mount - Grey - Travis Logo | | |
| 0.584.042 | GTMFL | Proflame 2 | Hand Held - Silver | | |
| 0.584.045 | GTMFL | Proflame 2 | Wall Mount - Black | | |
| 0.584.049 | GTMFL | Proflame 2 | Wall Mount - White | | |
| 0.584.043 | GTMFSL | Proflame 2 | Wall Mount - Black - Travis Logo | | |
| 0.584.040 | GTMFSLA | Proflame 2 | Hand Held - Silver | | |
| 0.584.080 | GTMFSLA | Proflame 2 | Hand Held - *Connect Features - Silver | | |
| 0.584.044 | GTMFSLA | Proflame 2 | Wall Mount - Black | | |
| 0.584.048 | GTMFSLA | Proflame 2 | Wall Mount - Smart Start - Black | | |
| 0.584.090 | GTMFSLA | Proflame 2 | Wall Mount - Connect Features - Black | | |

| Receivers | | | |
|-----------|---------|--------------------------|---|
| Part #s | Version | System | Additional Info |
| 0.584.221 | GT | Proflame 1 Proflame 2 | Receiver Box only |
| | GTM | | |
| | GTMF | | |
| 0.584.521 | GT | Proflame 1 Proflame 2 | Kit - Includes 0.584.221 receiver, wall plates, screws, batteries, and instructions. |
| | GTM | | |
| | GTMF | | |
| 0.584.516 | GT | Proflame 1 Proflame 2 | Kit w/ Remote - Includes 0.584.021 (GT) remote, 0.584.221 receiver, wall plates, screws, batteries, and instructions. |
| | GTM | | |
| | GTMF | | |
| 0.584.525 | GT | Proflame 1 Proflame 2 | Has antenna connection (small hole next to Molex connector). Kit - Includes receiver, wall plates, screws, batteries, and instructions. |
| | GTM | | |
| | GTMF | | |
| 0.584.524 | GTMF | Proflame 1 Proflame 2 | Has Timed Fan Feature (used with FCM). Kit - Includes receiver, wall plates, screws, batteries, and instructions. |
| | GTMFS | | |
| 0.584.523 | GTMFS | Proflame 1 Proflame 2 | Kit - Includes receiver, wall plates, screws, batteries, and instructions. |

| FCM (Fan Control Module) | | |
|--------------------------|---------|------------|
| Part #s | Version | System |
| 0.584.121 | GTMF | Proflame 1 |
| | GTMFS | |

| Stepper Motors | | | | |
|----------------|---------|------------|---------------|-----------------|
| Part #s | Version | System | Ignition Type | Additional Info |
| 0.907.843 | GTM | Proflame 1 | CPI | NG |
| | GTMF | | | |
| | GTMFS | | | |
| 0.907.844 | GTM | Proflame 1 | CPI | LP |
| | GTMF | | | |
| | GTMFS | | | |

| | | | | |
|-----------|--|--------------------------|-----|--------------------|
| 0.907.013 | GTM GTMF GTMFS GTMFL GTMFSL GTMFSLA | Proflame 1 Proflame 2 | IPI | NG 1.6 - 3.5" w.c. |
| 0.907.017 | GTM GTMF GTMFS GTMFL GTMFSL GTMFSLA | Proflame 1 Proflame 2 | IPI | NG 2.2 - 3.5" w.c. |
| 0.907.023 | GTM GTMF GTMFS GTMFL GTMFSL GTMFSLA | Proflame 1 Proflame 2 | IPI | NG 1.1 - 3.8" w.c. |
| 0.907.012 | GTM GTMF GTMFS GTMFL GTMFSL GTMFSLA | Proflame 1 Proflame 2 | IPI | LP 6.4 - 10" w.c. |
| 0.907.015 | GTM GTMF GTMFS GTMFL GTMFSL GTMFSLA | Proflame 1 Proflame 2 | IPI | LP 2.9 - 11" w.c. |

| Wire Harness | | | | |
|--------------|--------------------|---------------------------|---------------|---|
| Part #s | Version | System | Ignition Type | Additional Info |
| 0.584.901 | GT GTM | Proflame 1 | CPI | 750mm (2.5') |
| 0.584.902 | GT GTM | Proflame 1 | CPI | 3000mm (10') |
| 0.584.903 | GTMF GTMFS | Proflame 1 | CPI | 750mm (2.5') |
| 0.584.904 | GTMF GTMFS | Proflame 1 | CPI | 3000mm (10') |
| 0.584.911 | N/A | Proflame 0 DCF Modules | IPI | For DFC modules w/o remote system. Includes main harness and pilot ground wire |
| 0.584.912 | N/A | Proflame 0 DCF Modules | IPI | For DFC modules w/o remote system. Includes main harness, pilot ground wire, and CPI Switch |
| 0.584.906 | GT GTM GTMS | Proflame 1 | IPI | Connection for AC or DC power supply. 750mm (2.5') |
| 0.584.850 | GT GTM GTMS | Proflame 1 | IPI | AC Power Adapter Only |
| 0.584.905 | GTMF GTMFS | Proflame 1 | IPI | FCM power connection. 750mm (2.5') |
| 0.584.907 | GTMF GTMFS | Proflame 1 | IPI | FCM power connection. 3000mm (10') |
| 0.584.921 | GTMFSL GTMFSLA | Proflame 2 | IPI | Split Flow wire harness. |
| 0.584.920 | Main harness P2 | Proflame 2 | IPI | Connections for valve, battery, and CPI. APS jumped |
| 0.584.924 | Main harness P2 | Proflame 2 | IPI | Connections for valve and battery. CPI and APS jumped |
| 0.584.922 | N/A | Proflame 2 | IPI | Alternative Battery Holder / Switch wiring harness |

Split Flow Valve

| Part #s | Version | System | Ignition Type | Additional Info |
|-----------|----------------------------|--------------------------|---------------|-------------------------|
| 0.540.001 | GTMFS GTMFSL GTMFSLA | Proflame 1 Proflame 2 | CPI IPI | 9/16 UNEF Outlet Thread |
| 0.540.002 | GTMFS GTMFSL GTMFSLA | Proflame 1 Proflame 2 | CPI IPI | 3/8 NPT Outlet Thread |

DFC Modules

| Part #s | FFRT | PoD | System |
|-----------|------------|-----|------------|
| 0.584.302 | Instant | No | Proflame 1 |
| 0.584.602 | Instant | Yes | Proflame 1 |
| 0.584.621 | 5 Seconds | Yes | Proflame 0 |
| 0.584.322 | 5 Seconds | No | Proflame 1 |
| 0.584.622 | 5 Seconds | Yes | Proflame 1 |
| 0.584.303 | 10 Seconds | No | Proflame 1 |
| 0.584.603 | 10 Seconds | Yes | Proflame 1 |

IFC Modules

| Part #s | Version | FFRT | PoD | System | Additional Info |
|-----------|----------|------------|-----|------------|--|
| 0.584.307 | Basic | Instant | No | Proflame 2 | |
| 0.584.607 | Basic | Instant | Yes | Proflame 2 | |
| 0.584.327 | Basic | 5 Seconds | No | Proflame 2 | |
| 0.584.627 | Basic | 5 Seconds | Yes | Proflame 2 | |
| 0.584.306 | Standard | Instant | No | Proflame 2 | |
| 0.584.606 | Standard | Instant | Yes | Proflame 2 | |
| 0.584.326 | Standard | 5 Seconds | No | Proflame 2 | |
| 0.584.336 | Standard | 5 Seconds | No | Proflame 2 | |
| 0.584.626 | Standard | 5 Seconds | Yes | Proflame 2 | |
| 0.584.636 | Standard | 5 Seconds | Yes | Proflame 2 | Smart Start |
| 0.584.666 | Standard | 5 Seconds | Yes | Proflame 2 | Smart Start & Proflame Connect Feature |
| 0.584.308 | Standard | 10 Seconds | No | Proflame 2 | |
| 0.584.608 | Standard | 10 Seconds | Yes | Proflame 2 | |
| 0.584.305 | Complete | Instant | No | Proflame 2 | |
| 0.584.605 | Complete | Instant | Yes | Proflame 2 | |
| 0.584.325 | Complete | 5 Seconds | No | Proflame 2 | |
| 0.584.625 | Complete | 5 Seconds | Yes | Proflame 2 | |
| 0.584.665 | Complete | 5 Seconds | Yes | Proflame 2 | Smart Start & Proflame Connect Feature |

Misc

| Part #s | Version | System | Ignition Type | Additional Info |
|------------------|---------|------------|---------------|---|
| 0.584.103 | N/A | Proflame 2 | IPI | Alternative Battery Pack with Switch. |
| N/A Generic part | N/A | Proflame 2 | IPI | Normal battery pack is any 6v battery pack with 9v connector. |