

Harman Advance-2

Older Harman Advance units (made before HHT purchased the company) do not have an igniter. The rating plate on the back of the stove might not say Harman. The Advance-2 has an igniter.

Regardless, older Harman Advance units and Advance-2 units will use the same parts as the current Harman Advance.

CE **GUARDIAN** LISTED PELLET FUEL BURNING ROOM HEATER
MODEL: "ADVANCE-2"
GL-010117
DO NOT REMOVE THIS LABEL

TESTED TO : UL 1482
ASTM E1509
OREGON 814-23-900
ULC-S627, WH-PN 025
TEST DATE: JUNE 1999
European Standards
Tested by EMITECH, APAVE and
BFP Electronique
EN 550 14-1, EN 550 14-2, CEI 335-1
TEST DATE: MARCH 2000

Minimum clearances to combustibles:
Sidewall to stove 10"
Backwall to stove 1"
Ceiling to stove top 24"
Stove corner to diagonal wall 7"
Prevent house fires, operate with viewing & ash door closed.
Unit must be placed on a non-combustible floor protector
extending 6" to the front, 6" to sides and 1" to rear.
Exhaust type: Listed type PL vent installed to vent
manufacturer's instructions and local building codes.
Electrical rating for USA: 120 volts, 60 hz, 480 Watts
Fuse Rating for USA: 6 A
Electrical rating for UK: 230/250 volts, 50 hz, 480 Watts
Fuse Rating for UK: 3 A
Fuel: Pelletized or biomass
Install and use only in accordance with manufacturer's
installation and operating instructions. Contact local building
or fire officials about restrictions & installation inspection in
your area.
Epa exempt per 40 cfr 60.534, method 28a.
Approved for use in mobile homes.
Input rating: 6.0 lbs per hour.
Replace glass only with ceramic glass.
DO NOT CONNECT THIS UNIT TO A CHIMNEY

INSTALL WITH MINIMUM CLEARANCES TO WALLS AS SHOWN

FLOOR PROTECTOR MINIMUM SIZE 1"

SIDEWALL-BACKWALL INSTALLATION 1"

CORNER INSTALLATION 7"

APPAREIL DE CHAUFFAGE MODELE: "NE PAS ENLEVER C

NORMES EUROPEENNES
Tests realises par EMITECH, APAVE et BFI
EN55014-1
EN55014-2
CEI335-1
TEST DATE: Mars 2000

DISTANCES MINIMUM DE SECURITE
Mur lateral - Poeele
Mur arriere - Poeele
Plafond - Dessus poeele
Mur - Angle poeele en diagonale
Pour ecarter tout risque d'incendie, utiliser
et cendrier fermes.
L'appareil doit etre installe sur une paroi
non combustible qui depasse le poeele de 160 mm
cotes et de 25 mm derriere.

EVACUATION DES GAZ: Respecter
fabricant de tuyaux et les regles de
localement.

CARACTERISTIQUES ELECTRIQUES: 230V
COMBUSTIBLE: Granules de bois
Respecter scrupuleusement les instructions
pour l'installation et les consignes de
sécurité. Respecter les regles de securite en vigueur
EPA EXEMPT N° 40 RFC - #60 534 (me
Peut etre installe en mobile homes.
Consommation: 2,7 kg/heure
En cas de remplacement de la vitre, n'utiliser
que du verre ceramique.

**NE PAS RACCORDER CE POELE A UN CONDUIT DE
CHEMINEE UTILISE POUR UN
AUTRE APPAREIL.**

**MAN
HAR
352 A
HALIF**