

67FAK

Fresh Air Kit

The 67FAK Fresh Air Kit should be installed through an outside wall. It must exit into a well ventilated area and not into another room. Check for electrical wiring, plumbing or other obstructions before drilling or cutting into the wall.

DO NOT alter the structural integrity of the wall. Consult the "American Harvest" owner's manual for more information.

Mounting Instructions:

Remove contents from the carton. Contents should include: 1_Outside Cover Assembly (A), 1_Rodent Cover (B), 1_Flexible Hose (C), 2_Hose Clamps (D), 1_Inside Cover (E), 1_Adapter (F), 4_Wall Anchors, 8_3/4" screws.

Step 1

Determine the location of the hole through which the Fresh Air Kit will enter the room.

Step 2

Cut a 2-1/4" Diameter hole in the wall.

Step 3

Attach the flexible hose to the Outside Cover Assembly (A) with one of the 2" hose clamps (D). Then using the appropriate screw for your wall application, attach the Rodent Cover (B) and Outside Cover Assembly to the wall. Screws have been provided if acceptable to your wall application.

Step 4

Slide the Inside Cover (E) over the flexible hose and attach to the inside wall. Screws have been provided if acceptable to your wall application.

Step 5

Remove the rear of the pedestal on your heater by taking out the four screws holding it in place. Insert the Adapter (F) through the hole from the back side of the pedestal back as shown; then bend the three tabs down. Attach the other end of the flexible hose to the adapter with the remaining hose clamp. Reattach the pedestal back to the rear of the heater as removed.

